



Vertical IEC PDU

- Tough aluminium extrusion
- Shrouded switch and switch cover
- C14, C20, or 16A commando options
- 3m 1.5mm cable

Vertical IEC PDUs are widely used to accommodate cabinets where a higher number of IEC sockets are needed, but rack space is also at a premium. Being mounted at the back of the cabinet means that the PDU maintains a '0U' profile, allowing the rest of the cabinet to be populated with critical hardware.

Standard products

Order Code


Product Description

VIEC/6	6-way IEC C13 10A power with switch to 3-metre lead to 13A plug
VIEC/8	8-way IEC C13 10A power with switch to 3-metre lead to 13A plug
VIEC/10	10-way IEC C13 10A power with switch to 3-metre lead to 13A plug
VIEC/12	12-way IEC C13 10A power with switch to 3-metre lead to 13A plug
VIEC/16	16-way IEC C13 10A power with switch to 3-metre lead to 13A plug
VIEC/20	20-way IEC C13 10A power with switch to 3-metre lead to 13A plug
VIEC/24	24-way IEC C13 10A power with switch to 3-metre lead to 13A plug

PDU options



IEC C14



IEC C20



16A commando

PDU technical data

Weight of PDU	1.15kg – 1.5kg
Net length of PDU	VIEC/6; VIEC/8; VIEC/10; VIEC/12 : 490mm VIEC/16: 590mm VIEC/20: 700mm VIEC/24: 810mm
Net width of PDU	60mm
Net depth of PDU	45mm
Shipping length of PDU	520mm – 825mm
Shipping Width of PDU	132mm
Shipping Depth of PDU	75mm
Shipping Weight of PDU	1.3kg – 1.85kg
PDU max power	3250W
Output rating	10A
Overall rating	16A
Input Frequency	50/60Hz
Acceptable Input Voltage	250VAC