



## 32A UK PDUs

Picture shows V13A/12/32A

- Tough 1.5U aluminium extrusion
- Neon 'power on' indicator
- Upgraded internal 2.5mm ring wiring
- 3-metre 4mm lead

In areas of mass power usage such as data centres and comms rooms, 32A power feeds are often utilised, 32A PDU's are an upgraded version of the product designed for up to 16A, using 4mm cable externally and 2.5mm internally wired as a 'ring' the 32A PDU's can handle double the power input of the standard PDU.

### Standard products

*Order Code*

*Product Description*

H13A/6/32A

Horizontal 6-way UK PDU with 3m 4mm lead to 32A commando plug

V13A/8/32A

Vertical 8-way UK PDU with 3m 4mm lead to 32A commando plug

V13A/10/32A

Vertical 10-way UK PDU with 3m 4mm lead to 32A commando plug

V13A/12/32A

Vertical 12-way UKPDU with 3m 4mm lead to 32A commando plug

V13A/16/32A

Vertical 16-way UK PDU with 3m 4mm lead to 32A commando plug

V13A/20/32A

Vertical 20-way UK PDU with 3m 4mm lead to 32A commando plug

### PDU technical data

Weight of PDU	1.7kg – 2.65kg
Net length of PDU	486mm – 1330mm
Net width of PDU	65mm
Net depth of PDU	45mm
Shipping length of PDU	540mm – 1385mm
Shipping Width of PDU	142mm – 155mm
Shipping Depth of PDU	65mm – 75mm
Shipping Weight of PDU	1.85kg – 3.2kg
PDU max power	8000W
Output rating	13A
Overall rating	32A
Input Frequency	50/60Hz
Acceptable Input Voltage	250VAC